#### UNCLASSIFIED

	AD NUMBER
	AD044460
	CLASSIFICATION CHANGES
TO:	UNCLASSIFIED
FROM:	CONFIDENTIAL
	LIMITATION CHANGES

#### TO:

Approved for public release; distribution is unlimited. Document partially illegible.

#### FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; OCT 1954. Other requests shall be referred to Picatinny

Arsenal, Dover, NJ. Document partially illegible.

#### **AUTHORITY**

AGC D/A ltr 27 Dec 1974 ; AGC D/A ltr 27 Dec 1974

THIS REPORT HAS BEEN DELIMITED

AND CLEARED FOR PUBLIC RELEASE

UNDER DOD DIRECTIVE 5200.20 AND

NO RESTRICTIONS ARE IMPOSED UPON

ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

## UNCLASSIFIED

AD

CLASSIFICATION CHANGED

TO: UNCLASSIFIED

FROM: CONFIDENTIAL

AUTHORITY:

UNCLASSIFIED

# Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

AD ALAGA ALAGA

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U.S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by DOCUMENT SERVICE CENTER

PHOTI BULLDING TOTALER 2 OHIO

## Best Available Copy

# NO NO. 44 60 ASTIN FILE COPY

#### CONFIDENTIAL

TECHNICAL REPORT 2075

# THE IMPLUENCE OF THE SURFACE CONTIOUR OF AN EXPLODING BODY ON FRAGMENT DISTRIBUTION

BY

WILLARD R. BENSON

#### OCTOBER 1954



This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

SAMUEL FELTMAN AMMUNITION LABORATORIES
PICATININY ARSENAL
DOVER. N. J.

ORDNANCE PROJECT TBI-0004 DEPT. OF THE ARMY PROJECT 572-01-004

COPY 28

CONFIDENTIAL 54AA

65047

## THE INFLUENCE OF THE SURFACE CONTOUR OF AN EXPLODING BODY ON FRAGMENT DISTRIBUTION

by

Willard R. Benson

October 1954

Picatinny Arsenal

Dover, N. J.

Technical Report 2075

Ordnance Project No TB1-0004

Dept of the Army Project No 572-01-004

JOHN DE ARMITAG

Col, Ord Corps

Director

Approved:

Samuel Feltman

Ammunition Laboratories

54AA

65047

#### TABLE OF CONTENTS

	Page
Abstract and Conclusion	1
Symbols	2
Introduction	3
General Solution for Axis Perpendicular to Target Surface	5
Simplification of General Solution	8
Exact Solution for the Surface that Produces Constant Fragment Density	8
Fragment Distribution for a Spherical Missile	11
General Solution for Axis Inclined to Target Surface	12
Appendix A - Surface that Produces Optimum Lethal Area Under Certain Assumptions	18
Appendix B - Application of Analysis to an Aerial Exploding Body	22
Appendix C - Comparison of a Sphere and the Kent- Hitchcock Contour for Lethal Area	25

NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.

THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

CONFIDENTIAL

#### OBJECT

To determine the influence of the surface contour of an exploding body on fragment distribution.

#### ABSTRACT

The effect of the surface contour of an aerial expleding body upon fragment distribution is derived for a surface of revolution of arbitrary shape.

#### CONCLUSION

The density of the fragment distribution at any position on a target area can be determined for any given symmetrical surface contour of a missile. Generally, this distribution will be a variable.

The primary interest in desiring an analytical expression for fragment distribution is to determine its effect on lethal area. Naturally, the most desirable contour would be that which gives the maximum lethal area for a given number of fragments.

From the equations derived in this report, it is possible to determine the fragment distribution of a missile, given the equation or occordinates of the missile surface. If the fragment distribution is known, the lethal area for the particular tactical application intended for the missile can be calculated by using the information furnished in various Ballistic Research Laboratories (ERL) reports. In many cases, the computations could be set up in tabular form, so that a computer could carry out the calculations without understanding the physics of the problem.

#### SYMBOLS

x - Variable distance along x axis y - Variable distance along y axis r - Distance from origin to element ds Angle between r and the y axis b - Distance from x axis to the center of the radius of curvature for any element ds ρ - Radius of curvature for any element ds O- Angle between p and the y axis ↑ - Distance from x axis to the lowest point of the body h - Vertical distance from the lowest point of the body to the target surface T  $a - \lambda \neq h$ ds- An infinitesimal arc length d - Distance from the y axis to the x-intercept of the curve s  $\eta$  - Distance from the y axis to any arbitrary point on the target surface  $(-ay' \neq yy' \neq x)$ D - Diameter of the desired target area OP- Distance from the center of curvature of any element ds to point a on the target surface (see Fig 1) As- Surface area of the exploding body A - Projected area of the fragment M - Number of fragments per unit of the exploding body K - Density of the fragment distribution - number of fragments per unit area impinging on the target surface W - Weight of a fragment  $y^1 - dy/dx$  $y^{11} - d^2y/dx^2$  $B - (1 \neq (y^1)^2 - ay^{11} \neq yy^{11})$ R - Distances fragment travels from missile surface to target T - Target surface P - dy dx

#### INTRODUCT ION

- 1. The expected number of fragment hits on a target depends on the fragment density at the target and the projected area offered by the target. Whether the target is incapacitated or not depends on the mass, velocity, and shape of the fragments, in addition to the number and location of hits. This report will be concerned with only one of these factors, the fragment distribution. Since the most important factor in controlling fragment distribution is the surface contour of the exploding body, the analytical approach to the effect of the surface contour is considered, restricted by the following assumptions:
  - a. A constant number of fragments per unit surface area of the exploding body.
  - b. The fragments leave normal to the surface of the body
  - c. The velocities of the fragments are of such a high value that the influence of gravity can be neglected
  - d. The exploding body is considered stationary; that is, the body velocity is considered to be zero.

In order to obtain a simple mathematical solution to the problem, certain assumptions must be made. It is believed that the above assumptions are justifiable.

- 2. The first assumption, of course, can be controlled in the fabrication of the projectile.
- The second ascumption is certainly the most debatable. The location of the point of detonation will undoubtedly affect the normal radiation to some extent. If this influence is constant for a given design, however, as it should be, the fragment distribution, considering normal departure, should be susceptible to mathematical correction. All other influences on normal departure from a static body should be of a random nature and hence should fluctuate about the normal as an average.
- 4. The third assumption restricts the fragment paths to straight lines.


- 5. The fourth assumption is related to the second assumption in that any velocity of the body will affect the normal radiation of the fragments. In many cases, however, the velocity of the body will have little effect and can be neglected.
- 6. The mathematics of this paper were completed before the author realized that parts of it paralleled analytical work accomplished at the Ballistic Research Laboratories. The surface discussed in paragraphs 13-16 of this report is known as the Kent-Hitchcock contour.\*
- 7. In addition, H. K. Weiss \*\* of the Ballistic Research Laboratories has derived the optimum contour for certain tactical situations.

- \* Kent, R. H., "The Shape of a fragmentation Bomb to Produce Uniform Fragment Densities on the Ground," ERL Report No. 762
- \*\* Weiss, Herbert K., "Optimum Angular Fragment Distributions for Air-Ground Warheads," ERL Report 829

#### DISCUSSION OF RESULTS

#### General Solution for Axis Perpendicular to Target Surface

#### 8. General solution:



Consider that a missile of arbitrary shape, symmetrical about its axis, is detonated with its axis perpendicular to a plane target surface (see Fig 1). The density of the fragment distribution on the target surface T for any position  $\eta$  is given by

$$\frac{\mathbb{K} - MdA_s}{dA\eta} \tag{1}$$

where 
$$dA_s = 2 \pi x ds$$
 (2)

and 
$$dA_{\eta} = 2\pi \eta d\eta$$
 (3)

Substituting Equations 2 and 3 in Equation 1 gives

$$K = \frac{m \times ds}{\eta d\eta} \tag{4}$$

9. It now remains to find ds,  $\eta$ , and d $\eta$  as functions of x, y,  $y^1$  and  $y^{11}$ 

From Figure 1, it can be seen that

$$\eta = (R \neq \rho) \sin \theta - (\rho \sin \theta - r \sin \alpha)$$
 (5)

and that 
$$(R \neq \rho) = \frac{a-b}{\cos \theta}$$
 (6)

Substituting Equation 6 in Equation 5, there results

$$\eta = (a - b) \tan \theta - \rho \sin \theta r \sin \alpha \tag{7}$$

It is also noted that: 
$$b = r \cos \alpha - \rho \cos \theta$$
 (6)

Substituting Equation 8 in Equation 7, there results

$$\eta = a \tan \theta - r \cos \alpha \tan \theta \neq r \sin \alpha$$
 (9)

From elementary calculus the expression for the radius of curvature in rectangular coordinates is given by

$$\rho = -\left(\frac{1 + (y^1)^2}{y^1}\right)^{3/2} \tag{10}$$

Also from Figure 1, it is seen that

$$\frac{-dy}{dx} = \tan \theta \tag{11}$$

Therefore, 
$$\sin \theta = -\frac{y^1}{(1 \neq (y^1)^2)^{1/2}}$$
 (12)

10. By using Equations 10, 11, and 12, and since y = r cosec and x = r sin &, Equation 9 can be written as

$$\eta = - ey^1 \neq yy^1 \neq x \tag{13}$$

The following shows how dn varies with x, y and yl

$$d\eta = \frac{\partial r}{\partial x} dx + \frac{\partial r}{\partial y} + \frac{\partial r}{\partial y} dy^{1}$$
 (14)

or 
$$d\eta = \frac{\partial n}{\partial x} \quad dx \neq \frac{\partial n}{\partial y} \int \frac{\partial n}{\partial y} y^{1/2} dx$$
 (15)

Considering Equation 13, Equation 15 becomes

$$d\eta = (1 \neq (y^1)^2 - ay^{11} \neq yy^{11}) dx$$
 (16)

Furthermore, ds can be expressed as

ds • 
$$(1 \neq (y^1)^2)^{1/2}$$
 dx (17)

Finally, substituting Equations 13, 16, and 17 in Equation 4

there results 
$$K = \frac{x (1 \neq (y^1)^2)^{1/2}}{[x - (a-y) y^1]}$$
 (18)

From Equations 13 and 18, the density of the fragment distribution on target T can be obtained at any position of for any given surface contour of the exploding body.

11. The expression for the fragment distribution  $(K_n)$  normal to its path R at point p can be expressed simply as:

$$K_{n} = \frac{K}{\cos \theta} \tag{19}$$

or since 
$$\cos \theta = \frac{1}{(1 + (y^1)^2)^{1/2}}$$
 (20)

and considering Equation 18

$$Kn = \underbrace{Ax (1 \neq (y^{1})^{2})}_{(-ay^{1} \neq yy^{1} \neq x) (1 \neq (y^{1})^{2} - ay^{11} \neq yy^{11})}$$
(21)

whereas 
$$\eta = -ay^1 \neq yy^1 \neq x$$
 (22)

#### Simplification of General Solution

12. Although the solution obtained in the previous section is mathematically correct, in many cases it can be expressed in a form that is much simpler and nearly as accurate. This can be done by stating that:

$$R > P$$

$$R > r$$
(23)

therefore 
$$\eta = (R) \sin \theta = a \tan \theta = ay^{T}$$
 (24)

and 
$$\mathbf{a}_{\mathbf{q}} = \mathbf{a}_{\mathbf{y}} \mathbf{1}_{\mathbf{d}_{\mathbf{x}}}$$
 (25)

As a result, Equation 4 can be written

$$x = \frac{Mx(1 \neq (y^1)^2)^{1/2}}{a^2y^1y^{11}}$$
 (26)

also 
$$K_n = \underbrace{Ax(1 \neq (y^1)^2)}_{a^2y^1y^{11}}$$
 (27)

Where in both cases 
$$\eta = -ay^1$$
 (28)

This solution would no longer be justifiable for any surface for which  $\rho$  , such as a plane or a cone.

Exact Solution for the Surface that Produces Constant Fraguent Density

\* See Appendix A

<sup>13.</sup> In some cases, the most desirable surface is one that produces a fragment distribution of constant density when radiating upon the target area T\*. The ideal approach to this problem would be to formally solve the nonlinear differential Equation 18, treating K as a constant. This equation of course is satisfied by the surface y constant. There should, however, be another solution that would

result in a curved surface, the surface in which we are interested. This can be obtained by solving the approximate Equation 26, treating K as a constant, and keeping in mind the restrictions imposed upon this equation\*\*. The order of approximation of the solution of Equation 26 can be obtained by substituting the derived surface in Equation 18, thus obtaining the exact density of the fragment distribution produced by this surface. Equation 26 can be written

$$K a^2 p dp = x (1 \neq p^2)^{1/2}$$
 (29)

where  $p = \frac{dy}{dx}$ 

Transferming 
$$\frac{ka^2}{2A} \int (1 \neq p^2)^{-1/2} (2pdp) = \int xdx$$
 (30)

Upon integrating 
$$\frac{ka^2}{\sqrt{7}} (1 \neq p^2)^{1/2} = \frac{x^2}{2} \neq c$$
 (31)

14. Now consider the boundary condition

p) 
$$= 0$$
 Then  $C = \frac{ka^2}{M}$  (32)

Substituting for C in Equation 31 gives

$$\frac{ka^2}{4} (1 \neq p^2)^{1/2} = \frac{x^2}{2} \neq \frac{ka^2}{4}$$
 (33)

Squaring the above equation on both sides and solving for p,<sup>2</sup> there results

$$p^{2} = \frac{M^{2}}{hk^{2}a^{4}} (x^{2} / 2ka^{2})^{2} - 1$$
 (34)

Simplifying and solving for p gives

$$P = -(\frac{x^2}{A^2} \neq 2)^{1/2} = \frac{x}{A}$$
 (35)

\*\* It is of interest to note that the solution y = constant no longer satisfies this equation.

Where the negative sign is chosen outside the radical to conform with the chosen coordinate system and

 $\frac{2ka^2}{4} = A_1^2$ 

remembering that p = dy/dx, Equation 35 becomes

$$y = -\int \frac{(x^2 + 2)^{1/2}}{A_i} dx$$
 (36)

Upon integrating 
$$y = \frac{A}{3}$$
  $(\frac{x^2}{A_1^2} \neq 2)^{3/2} \neq c1$  (37)

15. Consider, now, the boundary condition

y) = 
$$0$$
 where  $\lambda$  is now considered  $\Theta$ .

$$0 = -A \cdot 8 \neq C_1$$
 (38)

O.P

$$c_1 = 0 \neq \underline{A}_1 = 8 \tag{39}$$

Substituting C<sub>1</sub> from Equation 41 into Equation 39 leads to the desired surface (Equation 40), which will produce a constant density of fragments, subjected to the assumptions made in paragraph 12.

$$y = -\Lambda ((x^2 \neq 2)^{3/2} - 2^{3/2})$$
 (See Fig 3) (40)

where 
$$A_{i} = a \left[ \frac{2k}{A} \right]^{1/2}$$
  
and  $\eta = a \left( \frac{x^{2}}{A^{2}} \neq 2 \right)^{1/2} \frac{x}{A_{i}}$  (41)

16. If for practical construction reasons (for example to allow space for a fuze well), a diameter (d) at the apex of the surface must be inoperative, it would be desirable to use the boundary p = 0 when x = D/2 when solving for the constant  $C_1$  in order to cut down on the dead space on the target surface.

Using this boundary condition in conjunction with Equation 31, there results

 $c = \frac{A^2}{2} - \frac{D^2}{8}$  (42)

Consequently 
$$\frac{A_1^2}{2} (1 \neq p^2)^{1/2} = \frac{x^2}{2} \neq \frac{A_1^2}{2} - \frac{D^2}{8}$$
 (43)  
and  $p^2 = (\frac{x^2}{4} \neq \frac{1}{4} - \frac{D^2}{4})^2 - 1$ 

or  $y = \int_{-\frac{\pi}{4A^2}}^{\frac{\pi}{4A^2}} \left[ (x^2 \neq 1 - 0^2)^2 - 1 \right]^{1/2} dx$  (44)

Equation 14 is the solution in integral form for this particular case. Given constants D and A, the desired surface is easily obtained by numerical integration.

#### Fragment Distribution for a Spherical Missile

17. The equation for a circle in polar coordinates is

$$y = \cos^{2}$$

$$x = \sin \theta \tag{45}$$

where r is a constant. When revolved about a diameter a spherical surface is generated.

It follows that 
$$y^{\frac{1}{2}} = \frac{\frac{dy}{d\theta}}{\frac{dx}{d\theta}} = \frac{\sin \theta}{\cos \theta} = \tan \theta$$
 (46)

and 
$$\mathbf{y^{11}} = \frac{\frac{d\mathbf{y^{1}}}{d\theta}}{\frac{d\mathbf{x}}{d\theta}} = \frac{-\sec^{2}\theta}{r\cos\theta} = \frac{-\sec^{3}\theta}{r}$$
 (47)

Substituting the values for x, yl, and y!! in Equation 26, there results

$$K = \underbrace{Mr^2}_{a^2} \cos^3 \theta \tag{48}$$

Letting 
$$\frac{Ar^2}{a^2} = \lambda$$


then 
$$K = \lambda \cos^3 \theta$$
 (49)

and expressed as a dimensionless ratio

$$\frac{K}{2}$$
 =  $\cos^{3\theta}$  (See Fig 4) (50)

Ceneral Solution for Axis Inclined to Target Surface

18. The solution obtained in paragraphs 8 to 11 is restricted in that the axis of the missile must be perpendicular to the target surface. Obviously, this is not always the case, and it becomes of interest to find out how the fragment distribution varies when the missile axis is inclined to the target surface.



F19.2

19. Consider Figure 2. The plane (eo'd) is perpendicular to line (oo'). It is desired to find the fragment density distribution on plane (go'd) which is inclined to line (oo'). The density K on plane (eo'd) at any point b is given by Equation 18, or by Equation 26 if the simplified solution is justified. The fragment density normal to R at point a is therefore

$$K_{n_a} = \frac{K}{\cos a} \frac{(ob)^2}{(oa)^2}$$
 (51)

However, (ob) can be expressed as

and (oa) as

(oa) = 
$$a \sin \frac{\Re /\alpha}{2} /\alpha$$
 =  $a \cos \alpha$  sin ( $\Re - e - \alpha$ ) cos ( $e /\alpha$ ) (53)

 $K_{\mathbf{n}_{\mathbf{a}}}$  can therefore be expressed as

$$K_{n_{\mathbf{a}}} = \frac{K \cos^{2} (\Theta / \alpha)}{\cos^{3}\Theta \cos^{2} \alpha} \tag{54}$$

and the fragment density on plane (go'd) at point a as

$$K_{a} = \frac{K \cdot \cos^{3}(6 + \beta C)}{\cos^{3} Q_{COS}^{2}}$$
 (55)

It is more convenient to express the angle & as a function of  $\phi$ , the angle the missile axis (00') makes with the normal to the target surface (go'd), and  $\phi$  the angle between planes (ogo') and (oao'). This can be done as follows

$$\sin \phi = \frac{bh}{bc} \tag{56}$$

But bc 
$$\bullet$$
 a tan  $\Theta$  cos  $\beta$  (57)

and bh = a tan 
$$\Theta$$
 sin  $C$  (58)

Consequently

(59)

20. In order to locate the position of our new fragment distribution (o'a) in terms of (o'b) must also be determined. From Figure 2, it is observed that:

$$\frac{\text{(o'a)}}{\sin(\frac{1}{2} + \theta)} = \frac{\text{(o'b)}}{\sin(\frac{1}{2} - \theta - \infty)}$$
(60)

or

$$\frac{(o^{\dagger}a)}{\cos\theta} = \frac{(o^{\dagger}b)}{\cos(\theta + \alpha)} \tag{61}$$

The (o'b) is  $\eta$  of the general solution in paragraphs 8 to 11, so by letting (o'a) =  $\eta$ '

there results 
$$\eta' = \frac{\eta \cos \theta}{\cos (\theta \neq \alpha)}$$
 (62)

The fragment density and location can be determined on the inclined target plane by using Equations 55, 59, and 62, as long as the distribution is known on the plane normal to the missile axis.

21. Since the striking velocity of a fragment is a function of the length of path traveled, the length of the new fragment path is also of interest. It can be expressed as

(oa) = 
$$\frac{a \cos \alpha}{\cos (\theta \neq \alpha)}$$
 =  $\frac{h \cos \alpha}{\cos \phi \cos (\theta \neq \alpha)}$ 

The length of the fragment path divided by the length of the path to the normal target plane is therefore

$$\frac{(oa)}{(ob)} = \frac{\cos \theta \cos \alpha}{\cos (\theta \neq \alpha)}$$
 (64)

22. Equations 55, 59, and 62 must be used to determine the effect of inclining the axis of the shape derived in paragraph 17. These equations are:

$$K_{a} = \frac{K \cos^{3} (\Theta \neq \alpha)}{\cos^{3} \Theta \cos^{2} \alpha}$$

$$\sin \alpha = \sin \theta \cos \beta$$
 (65)


where for this particular problem K is a constant.


23. For a given angle  $\phi$ ,  $K_{a/K}$  and  $\eta'/\eta$  could be plotted as

functions of 0 for various angles . If desired, a set of tables or graphs could be drawn up in this manner. It would then be a rather simple process to compute the lethal area as a function of the angle of inclination.

#### Inclosures:

- 1 2 Figures 3 and 4
- 5 7 Appendices A, B, and C (Appendix B contains Tables 1 and 2)





#### APPENDIX A

SURFACE THAT PRODUCES OPTIMUM LETHAL AREA UNDER CERTAIN ASSUMPTIONS (This problem was solved by Mr. H. K. Weiss")

The assumptions stated in the "Introduction" are assumed to hold, and in addition the axis of the missile is considered perpendicular to the target surface. The expected number of hits on a target can be expressed as:

$$E_h = \frac{M_0}{r^2}$$
 AQ (la)

ragments per unit area per unit distance from the burst point, at angle  $\theta$ 

distance the fragments travel to the target

exposed area of the target

The expected number of disabling hits is

$$E_k = E_h P_{hk}$$
 (2a)

where Phk is the conditional probability that a hit will disable the target. This is usually a function of the mass, velocity, and the presented area of a fragment. For mathematical simplicity, Phk will

be treated as a constant. This means that all the fragments are considered to have the same disabling potential.

By using the Poisson approximation, the probability of disabling The number of disabled targets is  $\int \int P_k dxdy$  where T is the

number of targets per unit area. If T is considered constant, it can be brought outside the integral. The integral term is then defined as the lethal area  $(A_{I})$ .

$$A_{L} = \int \int P_{k} dxdy$$
 (4a)

Weiss, H. K., op. cit.

If the lethal area is multiplied by the density of the targets, therefore, the number of targets disabled will be obtained. Equation 4a can be expressed in polar coordinates as

$$A_{L} = 2\pi a^{2} \int (1-e^{-3k}) \sin \theta \sec^{3} \theta d\theta$$
 (5a)

where

a - height of burst

0 = angle between missils axis and fragment path

It is convenient at this point to make the following change of variables

and 
$$dW = \cos \theta$$

Equation 5a becomes

$$A_{\rm L} = -2\pi a^2 \int (1-e^{-E_{\rm k}}) W^{-3} dw$$
 (6a)

Furthermore

$$\mathbf{E}_{\mathbf{k}} = \mathbf{E}_{\mathbf{h}} \mathbf{P}_{\mathbf{h}\mathbf{k}} = \frac{\mathbf{M}(\boldsymbol{\Theta}) \mathbf{A} (\boldsymbol{\Theta})}{\mathbf{r}^2} \mathbf{P}_{\mathbf{h}\mathbf{k}}$$
 (7a)

However

$$r = a/\cos \theta = aw^{-1}$$

$$\mathbf{E}_{\mathbf{k}} = \underline{\mathbf{M}(\boldsymbol{\Theta}) \mathbf{A} (\boldsymbol{\Theta})} \mathbf{W}^{2} \mathbf{P}_{\mathbf{h}\mathbf{k}}$$
 (8a)

If it is also considered that the exposed area varies as the  $\cos \theta_{\bullet}$  as would a flat target,  $i_{\bullet}$  can be expressed as

$$A_{\Omega} = A \cos \theta = Aw$$
 (9a)

Hence

$$\mathbf{E}_{\mathbf{k}} = \mathbf{M}_{\mathbf{w}} \mathbf{A} \mathbf{W}^{3} \mathbf{P}_{\mathbf{h} \mathbf{k}}$$

$$(10a)$$

and  $A_{L} = -2\pi a^{2} \int \left(1 - e^{\frac{-M_{A}W^{3}}{a^{2}}}\right)^{P_{hk}} w^{-3} dw$  (11a)

A small increment of area at some position (W), over a band width (SW) is

$$(dA_L)_{i} = -2\pi a^2 (1-e^{\frac{-M_WAW^3}{a^2}})^{P_{hk}} W^{-3} dW (12a)$$

If M is now increased at the point (W), over the band width (SW) the increase in (SAL) is

$$\delta(\delta A_{\rm L}) = \left[2\pi A P_{\rm hk} - \frac{-M_{\rm h}A^{-3}}{a^2}\right] \delta W \delta M \qquad (13a)$$

but since the total number of fragments must not increase,  $\sigma$  M must be subtracted at some other point ( $W_2$ ). At that point

$$\delta(\sigma A_L)_2 = \left[2\pi A P_{hk} e^{-M_W AW^3} P_{hk}\right] \delta W \delta M$$
 (114a)

The necessary condition for  $\mathbf{M}_{\!_{\mathbf{W}}}$  to be the surface that produces maximum lethal area is

$$\delta(\delta A_L) = \delta(\delta A_L) = 0$$
 (15a)

Therefore 
$$2\pi A P_{hk} = \frac{-N_W A W^3}{a^2} P_{hk}$$
 = C = constant (16a)

or 
$$\frac{M_{k}AN^{3}P_{hk}}{2} = \operatorname{Im}\left[\frac{2\pi A P_{hk}}{C}\right]$$
 (17a)

or 
$$\mathbf{M}_{\mathbf{w}} = \begin{bmatrix} \mathbf{a}^2 & \text{In} & (2 \mathbf{n} \mathbf{A} P_{\mathbf{h}_{\mathbf{k}}}) \end{bmatrix} \mathbf{w}^{-3}$$
 (18a)

Let 
$$\frac{a^2}{A P_{hk}}$$
 Ln  $(2 \pi A P_{hk})$  = A'

Then 
$$M_W = A^*W^{-3}$$
 (19a)

or 
$$M_{\Theta} = A^{\dagger} \sec^3 \Theta$$
 (20a)

Consider now the Kent-Hitchcock contour. It fulfilled the requirements that K = constant where

$$\frac{K = Axds}{\eta d\eta}$$
 (21a)

or 
$$K = \frac{M_0 \sin \theta d \theta}{\eta d\eta}$$
 (22a)

But  $\eta = a \tan \theta$ 

Therefore 
$$K = \frac{M_{\odot} \sin \Theta d \Theta}{a^2 \tan \Theta \sec^2 \Theta d \Theta}$$
 (23a)

or Mo can be expressed as

$$M_{\Omega} = Ka^2 \sec 3 \theta$$
 (24a)

Equation 21 has the form of Equation 20a. Therefore, the Kent-Hitchcock contour is the contour that produces optimum lethal area under the restrictions of this particular problem.

#### APPENDIX B

#### APPLICATION OF ANALYSIS TO AN AERIAL EXPLODING BODY

#### Problem

To find the proper surface contour of an aerial exploding body that will produce a fragment distribution of constant density over the target surface T under the following restrictions:

- 1. Height (h) of the exploding body above target = 20 ft
- 2. Desired density of the fragment distribution (k) over the target T = 1.67 fragments/ft2
- 3. Desired diameter (D) of target = 40 ft
- 4. Fragment weight = 2.5 grains
- 5. Surface area of fragment Af = .01175 in2
- 6. Fragment distribution (ℳ) on body surface =

The surface which satisfies this problem is that of Equation 40. For simplicity, however, let a = h and therefore  $\nearrow$  = 0. Equation 40 would then reduce to

$$y = -\frac{A}{3} \left[ (x^2 \neq 2)^{3/2} - (2)^{3/2} \right]$$
 (1b)

In order to establish the boundary of the body in the x direction, an additional equation concerning the surface area of the body is needed. This is expressed mathematically as

As = 
$$2 \int_{0}^{x} \pi(1 \neq (y^{1})^{2})^{1/2} x dx$$
 (2b)

where from Equation 33 it can be shown that

$$(1 \neq (y^1)^2)^{1/2} = (\frac{x^2}{4x^2} \neq 1)$$
 (3b)

Equation 2b can therefore be expressed as

As 
$$= 2 \int_{0}^{\infty} \frac{(x^3 \neq x)}{A^2} dx$$
 (4b)

Upon integrating As 
$$= (xo^{4} \neq xo^{2})$$

$$(5b)$$

Equation 5b can be expressed as

$$x_0^4 \neq 2A^2 \times x_0^2 - \frac{2A^2As}{4} = 0$$
 (6b)

where

$$A^2 = \frac{2ka^2}{85.106} = \frac{2(1.67)(20)^2}{85.106} = 15.698 in^2$$

and in this particular problem

As = 
$$\frac{\pi p^2}{4}$$
 ·  $kA_f = (\frac{40}{4})^2$  · (1.67)(.01175) = 24.658 in<sup>2</sup>

Substituting these values in Equation 6b and solving for  $x_0$  by using the quadratic formula, it is found that

$$x_0 = 2.550 \text{ in.}$$

By substitution of the value of A in Equation 40, the desired surface becomes

y = -1.3206 
$$\left[ (.06370x^2 \neq 2)^{3/2} -2.8284 \right]$$
 (7b)

from which 
$$y^1 = -.25237 \times (.06370x^2 \neq 2)^{1/2}$$
 (8b)

and 
$$y^{11} = -.01608 x^2 (.06370x^2 \neq 2)^{-1/2} -.25237 (.06370x^2)$$

$$\neq 2)^{1/2}$$
 (9b)

In order to find the exact density of fragment distribution on the target surface produced by Equation 7b, it is only necessary to substitute the above expressions in Equation 18. The results of

this substitution are presented in Table 1. It can be seen that he density of the fragment distribution is approximately 2% to 1% below the desired density of the fragment distribution. It is also seen that the target area is 3% larger than specified. This result suggests that the derived surface equation (1b) can be corrected to give improved results. It is proposed that the density of the fragment distribution be increased 3% by specifying that  $K^1 = 1.03K$ 

Then 
$$A^2 = 2 (1.03 \text{ ka}^2 = (1.03)(15.698) = 16.169$$
  
 $A = 4.021$ 

Hence, the corrected equation for y becomes

$$y = -1.34030 (.06185x^2 + 2)^{3/2} - 2.8284$$
 (10b)

and 
$$y^1 = -.24869x (.06185x^2 \neq 2)^{1/2}$$
 (11b)

$$y^{11} = -.01538x^2 (.06185x^2 \neq 2)^{-1/2} -.24869$$
  
(.06185x<sup>2</sup> \neq 2)<sup>1/2</sup> (12b)

Table 2 gives the improved results. The density of the fragment distribution now varies from  $\frac{1}{2}\%$  to -1%, while the target area is in error by less than  $\frac{1}{2}\%$ 

#### APPENDIX C

### COMPARISON OF A SPHERE AND THE KENT-HITCHCOCK CONTOUR FOR LETHAL AREA

From Appendix A it was shown that the Kent-Hitchcock contour produced the maximum lethal area for the type of problem considered. It remains of interest however to find how much greater this lethal area is than a conventional sphere. Consider the problem where the target radius (L) equals the burst height (a).

The distribution of fragments from a sphere is




Fig 5

The number of fragments over the target surface of radius L is

$$N_s = 2\pi K_0 \int_{-\infty}^{L} \cos^3 \theta \, r dr = 2\pi K_0 \int_{-\infty}^{L} \frac{L^3 \, r dr}{(r^2 \neq L^2)^{3/2}}$$
 (2c)

Where Ko is a constant that is a function of the burst height, radius of the sphere, and fragments per unit area on the sphere surface.

The number of fragments over the target surface of radius L from the Kent-Hitchcock contour is simply

$$N_{kh} = K_{kh} \pi L^2 \tag{3c}$$

	•
CONFIDENTI	
CORFIDERII	AL.

н	0	4.0	8.0	1.2	1.6	2.0	7.6	2 6
~	•	.15000	9,000	1.4400	2003	2		60.
2 200					7	3	36.	0.000
(.06370x f2)	2,000	2.0102	2.0408	2.0917	2,1631	2.254.80	0 2,3669	24142
(46.500.34 <sup>1/2</sup>	1.41/2	1.4180	1.4290	1.4463	1.4710	1.5010	1.5300	1.5540
3/5 (scares.)	2,8284	2.8512	2.9181	3.0253	3.1830	3.3618	3.6380	3.7528
(453m(+1)-1/2	1007.	12021	616693	17169-	08679	<u>.</u> 66822	2 265019	264350
	•	.0301	\$811	7,2600	£897°	₹7308	1.0692	1.220
· .		E11.	.2885	4380	0765	.7576	.9225	1.0000
x (+cme)-1/2	۰,	\$211.	6577	9566	1,7403	2.6649.	. 3.7451	4-1847
٦,	3569	-3597 ·	3,3678	3810	3992	11217	-448L	56575
<b>-</b>	•	75.75	69.240	105.12	142.56	181,82.	223.56	240.00
Įk.		· 00°	. 4£0.	77.	.278	.55	966	1.22
		34.748	70.07	106.43	144.44	184.37	226.95	243.77
, (4)	· 。,	50207	2692	. 8161	3528	25740	.8677	1,000
T.	85.656	86.328	. 88.272	91.440	95.308	101.208 107.616	107.616	110,280
T.	•	10.	100	660.	.187	.30	647	18.
9	959.98	87.359	89.399	92.731	97.348	103.090	109.963	112.841
$(1/(y^1)^2)^{1/2}$	1.000	1.010	1.041	1.092	1,163	1.255	1.367	1.4142
mx(1/(2),2)2/1/2	0	34.383	70.876	m.2	158.37	213.62	279.22	306.91
ار الارباء ال		3035.6 .01133	6264.6	9869.4 001130	14061	19007	24956	27507
K fr/ft <sup>2</sup>		1.632	1.629	1.627	1.621	1,619	1.611	~

6.503	2,4022	689	3	,, 316	ì	_														
				,64516		- 9829	4.1955	0057*	235.90	1.18	239.63	.9661	108.00	<b>*</b>	110.51	1.402	304.26	264,82	97170.	1.655
5.760	2,3563	1.5350	3,6168		-	.9162	3.7524	-4395	219.89	6.	223.26	*839v	105.48	97.	87.701	1.355	276.76		05110.	1.656
4.000	2,2474	1.4992	3.3696		£7254	.7457	2.6681	\$617	178.97	*	181.51	15561	99.336	300	101.19	1,247	212.25		201156	1,665
2.560	2.1583	1.4692	3.1713	79089*	%2% <del>-</del>	. 5846	1.7424	23922	140.30	12.	142.17	3418	94.128	.180	95.650	1,158	157.68		.01159	1,669
1.440	2,0691	1.454	3.01970	\$69185	-2564	.4313	-9963	3748	103.51	<b>1</b> .	104.82	.1860	89.952	<b>%</b> 0°	91.2%	1,089	m.22	9563.1	.01163	1.675
0.6400	2.03%	1,4281	2.9127	£70023	°773	.2841	1844	3620	481.89	œ0·	910*69	£0807	. 86.880	170	88.002	1.039	70.740	6073.5	.01165	1.678
0,1600	2.0099	1.4176	2.8488	-70541	£120 <del>2</del>	0171	1129	-3543	33.840	700°	34.244	-0198	85.032	600°	86.060	1,009	34.349	2947.0	.01166	1.679
0	2,0000	1.4142	2,8284	11/07.	0	•	°ı	3517	0	0	0	. 0	87.408	0	85.408	1.000	0	•		
<b>ነ</b> ት '	(.06185x²/2)	(461522.2) 1/2	(2018270) 3/2	(065824)-1/2	h	, <b>,</b> ,	x (mesta)-1/2	<b>\</b> F21	CON	'E	ENT		<b>1</b> , 7	a c		$1 \neq (y^2)^2$	$(1 \neq (x^1)^2)^{-1/2}$	8/6	fr/1m <sup>2</sup>	K fr/ft2
	0 0.1600 0.6400 1.440 2.560 4.000	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0099 2.0396 2.0691 2.1583 2.2474	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0099 2.0396 2.0891 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0399 2.0396 2.0891 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0396 2.0691 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .707117054127002369185269064266702	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0396 2.0391 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .7071170541370023669185668064466702 060273211302256445596472541	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0396 2.0394 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .70711 2.70541 2.70023 2.69185 2.69054 2.65702 0 20273 2.1130 2.2564 2.5596 2.7554 1	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0396 2.0391 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .70711 2.70541 2.70023 2.69185 2.68064 2.66702 0 20273 2.1130 2.2564 2.4596 2.4594 -0 11410 .2841 4.313 .5846 .7457	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0396 2.0396 2.0891 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .70711 2.70541 2.70023 2.69185 2.69064 2.65702 0 20273 2.1130 2.2564 2.5965 2.7254 1 0 11410 .284,1 4.313 .5846 7.457 -0 11410 .284,1 4.313 .5846 7.457 -0 33543 2.3620 2.3748 2.6681	x       0       0.1600       0.6400       1.440       2.560       4.000         (.06185x²/2)       2.0000       2.0099       2.0396       2.0691       2.1583       2.2474         (************************************	0 0.1600 0.6400 1.440 2.560 4.000 2.0000 2.0099 2.0396 2.0691 2.1583 2.2474 1.4142 1.4176 1.4281 1.4454 1.4692 1.4992 2.8284 2.8488 2.9127 3.01970 3.1713 3.3696 .70711 2.70541 2.70023 2.69185 2.68064 2.66702 0 20273 2.1130 2.2564 2.4596 2.7554 1.4597 -0 1410 3.2841 4.313 3.5846 3.7457 -0 33.840 68.184 103.51 140.30 178.97 219 0 33.840 68.184 103.51 140.30 178.97 219	(.06185x <sup>2</sup> /2) 2.0000 2.0099 2.0396 2.0691 2.1563 2.2474 (***********************************	(*************************************	(.06185x <sup>2</sup> /2)	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Comparation   Comparation	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$

,

To make a comparison of lethal area,  $N_{\rm kh}$  is assumed to be equal to  $N_{\rm g}$ . By equating these two expressions, it is found that

$$K_0 = K_{kh} = 1.706K_{kh}$$
 (140)

Lethal area can be expressed as (Equation 6a)

$$A_{L} = -2 \operatorname{re}^{2} \int (1 - e^{-Ek}) w^{-3} dw$$
 (50)

where

$$\mathbf{E}_{\mathbf{k}} = \mathbf{K} \mathbf{A}_{\hat{\mathbf{c}}} \mathbf{P}_{\mathbf{h}\mathbf{k}} \tag{6c}$$

Consider the  $A_Q = A \cos \theta = AW$ . The lethal area for a sphere is

$$A_{L/s} = 2 \pi A^2 \int (1 - e^{-1.706} A_{kh} P_{hk}^{-1}) W^{-3} dW$$
 (70)

since

$$K = K_0 W^3 = 1.706 K_{kh} W^3$$

where

The lethal area for the Kent-Hitchcock contour can be expressed as

$$A_{L} \setminus_{KH} = 2\pi a^{2} \int (1-e^{-AK_{kh}P_{hk}N}) N^{-3dw}$$
 (8c)

Assume AKkhPhk = 2.5 (This is a fair value for a sample problem)

Then

$$\frac{A_{L}}{2\pi a^{2}} = \int (1-e^{-\frac{1}{4} \cdot 26W^{\frac{1}{4}}}) W^{-3} dW$$
 (9c)

$$\frac{A_{L}}{2\pi a^{2}}\Big|_{kh} = \int (1-e^{-2.5\%}) W^{-3}dW \qquad (100)$$

Further assuming that the limit of the target area corresponds to  $\theta = 45^{\circ}$ , then the limits on the above integration are 1 to  $\cdot 707$  since W = cos  $\theta$ . Carrying out the above integration numerically, there results

$$A_{L/kh}$$
 = 1.166 (11c)

That is, the Kent-Hitchcock contour gives a lethal area that is 16.6% greater than a sphere, assuming that both surfaces contain the same number of fragments.

#### DISTRIBUTION LIST OF PICATINNY ARSENAL TECHNICAL REPORT 2075

	Copy No.
Commanding Officer	
Picatinny Arsenal Dover, New Jersey	
ATTN: Technical Information Section	1 - 5
Chief of Ordnance	
Department of the Army	
Washington 25, D. C.	
ATTN: ORDTB - Bal Section	6 - 11
Department of the Navy	
Bureau of Ordnance	
Washington 25, D. C. ATTN: Re3	10 15
ATTM: NO)	12 - 15
Commander	
U. S. Naval Ordnance Laboratory	
White Oak	
Silver Spring, Maryland ATTN: Library	2/ 20
Alla: Diblary	16 - 17
Commander	
Naval Ordnance Test Station	
Inyokern, China Lake	
California ATTN: Technical Library Branch	18
Allie leadinical biblary branch	16
Commander	
U. S. Naval Proving Ground	
Dahlgren, Virginia ATTN: M. I. Division	
ATTN: M. I. DIVISION	19
Office of Naval Research	
Department of the Navy	
Washington 25, D. C.	
ATTN: Scientific Documents Office (408)	
011108 (400)	20 - 21
Superintendent	
Naval Postgraduate School	
Monterey. California	20

#### COMMENTAL

	Copy No
Department of the Air Force	
Headquarters U.S.A.F.	
Washington 25, D. C.	
ATTN: Strategic Vulnerability	
Branch, DCS/Operations	23
	-,
Department of the Air Force	
Headquarters U.S.A.F.	
Washington 25, D. C.	
ATTN: DCS/O - Operations	
Analysis Division	24
Armed Services Technical Information Agency	
Documents Service Center	
Knott Building	
Dayton 2, Ohio	
ATTN: DCS-SD	
300 55	25 <b>-</b> 29
Director	
Weapons System Evaluation Group	
Office, Secretary of Defense	
Washington 25, D. C.	30
Chief of Army Field Forces	
Ft. Monroe, Virginia	
ATTI Pescench & Development Division	_
ATTM: Research & Development Division	31
Commanding General	
Redstone Arsenal	
Huntsville, Alabama	<i>3</i> 2
Commanding Officer	-
Frankford Arsenal	
Bridge and Tacony Streets	
Philadelphia 37, Pennsylvania	
Je sindy I vania	33
Commandant	
The Artillery School	
Ft. Sill Oklahoma	34
	24
Commanding Officer	
Watertown Arsenal	
Watertown 72, Massachusetts	35
one who are on the	"
Department of Ordnance	
J. S. Military Academy	
West Point, New York	76

	Copy No
Commandant	
U. S. Marine Corps	
Washington 25, D. C.	37 - 38
Operations Research Office	
Johns Hopkins University	
6410 Connecticut Avenue	
Chevy Chase, Maryland	39
Director	
Air Weapons Research Center	
Museum of Science and Industry	
University of Chicago	
Chicago 37, Illinois	
Thru: Chief, Chicago AFPFO	
209 Jackson Blvd.	
Chicago 6, Illinois	40
Ballistic Research Laboratories	
Aberdeen Proving Ground	
Maryland	41